


A114S/1120

Mounting frame for wall-hung WC and sensor





Application

For automatic flushing systems – sensor

For mounting in front of a support wall or in to a plasterboard construction with

preparation for mounting the sensor flusher

For wall-hung WC with a connecting pitch of 180 mm or 230 mm

Features

- The frame allows the anchoring to a separate sufficiently strong plasterboard partition, in front of the bearing wall
- Material: powder-coated metal
- Adjustable anchor feet and a spring-lock system, with a range of 0–200 mm
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Universal sensor holder compatible with other types of sensors

Scope of supply

- Fixation material for fixing the WC pan: threaded rod M12 2 pcs, washers 4 pcs , cover 2 pcs, nut 2 pcs, thread protector 2 pcs
- Fixation set: screw Ø8×60 4 pcs, dowel Ø12 4 pcs
- Waste elbow set HT 90/110 polypropylene
- Water supply joint to the WC pan HT 40
 Bracket for mounting the sensor
- Self-supporting frame
- Pipe for water supply to the WC pan from the flusher HT40

Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
A114S/1120	8595580518585	12,93 12,93 214,0 kg	1125×515×75 1125×515×75 mm	1 15 pcs

Warranty

2/15 years *

Technical specifications

Load test 400 kg