

AGV4

Rain drum 300×155/125/110 mm straight outlet, black

Application

For installation outside buildings For draining the rainwater and surface water to sewerage system For connecting gutter downspouts


Features

- Color: black
- Limits the transmission of the odours from the sewer
- Eccentric rings for connecting the gutter downspouts 80, 90, 100, 110 and 125
 mm
- Material: polypropylene enriched with glass fiber resistant to mechanical, chemical and thermal damage
- Option to buy a stainless steel basket against the invasion of rodents from the waste
- Option to buy a universal insert for round and square gutter downspouts
- Plastic basket can be easily removed and cleaned
- After installation in the interlocking pavement, the visible parts of the rain drum can be swapped for parts in gray colour
- Direct connection to waste 110, 125 mm
- Steeper gradient of the rain drum body enables a faster and bigger water flow towards the sewer
- Dry odour trap
- The lock prevents unintentional opening of the lid, overflow of water during heavy rains

Scope of supply

- The flap limiting the transmission of the odours from the sewer
- Basket for catching dirt and leaves
- Set of inlet rings for gutter downspouts diameter 80, 90, 100, 110, 125 mm
- Drain body DN110/125 mm straight outlet
- Lid with lock





Order number, Logistic information

,		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
AGV4	8595580519285	1,24 4,97 94,6 kg	315×335×165 655×335×345 mm	4 60 pcs

Warranty

2/6 years * EN 1253, EN 1451

Technical specifications

■ Flow rate 420 l/min