


APV5411

Floor drain 150×150/50 mm side outlet, stainless steel grid, wet odour trap





Application

For wheelchair access

For draining a single shower at floor level

For the interior, where will be frequent use associated with the regular water

runoff into the floor drain (bathrooms)

Features

- Side connection to waste Ø50 mm
- Insulation collar for connection to waterproofing of the building
- Compatibility with floor drains parts including wet, dry and combined odour trap SMART
- Material: stainless steel AISI 304, DIN 1.4301
- Material: polypropylene resistant to mechanical, chemical and thermal damage

EN 1253

- Mechanically cleanable trap up to the waste pipe
- Stainless steel grid 143×143×5 mm
- Wet odour trap prevents the penetration of odours from the sewer
- Height adjustable throat 22–110 mm

Scope of supply

- Floor drain throat 150×150 mm
- Stainless steel grid
- Seal kit

2/6 years *

- Floor drain body Ø50 mm, side outlet
- Wet odour trap

Order number, Logistic information

		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
APV5411	8595580520762	0,66 9,96 179,3 kg	150×150×101 590×430×390 mm	15 240 pcs
M/a usa satu .	N. a. una a			

Technical specifications

- Total installation height 101-189 mm
- Resistance of odour trap against the pressure 480 Pa
- Waste pipe diameter 50 mm
- Flow of the inlet grid 46 l/min
- Wet odour trap 51 mm

^{*} For more information about warranty visit https://www.alcadrain.com/warranty.

© 2025 Alcadrain s.r.o | Changes in dimensions and design reserved. | www.alcadrain.com