


A566-112122-120

Bath waste and trap for whirlpool bathtubs, chrome



Application

For whirlpool baths
To drain the water from the bath to the waste
For bathtubs with drain outlet Ø52 mm

Features

- The length of the bathtub trap 120 cm
- Overflow flexi pipe
- Compatible with most whirlpool and pearl systems
- For connection serve two outlets – standard elbow
- A part of the bath waste and trap is a mechanism, that when you open the drain outlet concurrently the valves open, so that can easily drain the residual water from the whirlpool bathtub
- Closing waste by pop-up mechanism
- Wet odour trap with swivel elbow

Scope of supply

- Assembly kit
- Chrome-plated stainless steel outlet grid
- Chrome-plated plastic control knob
- Chrome-plated plastic plug
- Standard elbow for connection of HMS 2 pcs
- Waste and trap body with overflow and discharge mechanism for HMS
- Profiled seal
- Odour trap of polypropylene, thermally and chemically resistant, longitudinally welded

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
A566-112122-120	8595580541149	112122 mm 0,73 8,79 160,6 kg	380×95×210 mm	12 192 pcs

Warranty

2/3 years *

Norms

EN 274

Technical specifications

- Resistance of odour trap against the pressure 588 Pa
- Flow rate 48,6 l/min
- Overflow flow rate 42 l/min
- Thermal resistance 95 °C
- Odour trap 50 mm