

APZ5-TWIN-1050 Spa

Waste system for installation in walls, cover for embedding tiles

Application

For wheelchair access

For installation into the wall

For indoor use


Suitable for areas with movement of large number of people – swimming pools, spa, wellness center

Features

- Completely cleanable trap up to the waste pipe
- Complete technical and design solutions
- Possibility to buy a combined odour trap
- COMPLETE PACKAGE INCLUDING ALL ACCESSORIES
- Linear drain from stainless steel (hardened by pickling, passivation and electrochemical polishing)
- Waterproof adhesive tape part of the packaging
- Trap firmly connected to the drain – 100% waterproofing
- Installation depth 64 mm
- Including easily removable cover - for insertion into the thickness of 12 mm
- Water flows into the drain only between the edge of the floor tiles and the cover of the drain system
- 25 years guarantee

Scope of supply

- Fixing hardware for anchoring the adjustable legs: screw M6x12 – 2 pcs
- Anchoring set: screw Ø6x50 – 2 pcs, dowel Ø10 – 2 pcs, screw Ø4.2x38 – 3 pcs, dowel Ø8 – 3 pcs
- Installation channel cover
- Stainless steel cover for embedding tiles
- The collar and the odour trap inlet are covered by the protective foil
- Self-adhesive waterproofing tape
- The shower drain is assembled with the odour trap



Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
APZ5-TWIN-1050	8595580553739	6,15 49,23 167,7 kg	1120x160x205 mm	8 24 pcs

Warranty

2/25 years *

Norms

EN 1253

Technical specifications

- Total installation height 165-220 mm
- Minimum thickness of concrete 100 mm
- Resistance of odour trap against the pressure 982 Pa
- Waste pipe diameter 50 mm
- Flow rate 60-68,8 l/min
- Cover width 60 mm
- Installation depth 64 mm
- Odour trap 50 mm