

# AM119/850 Renovmodul

Pre-wall installation system for building into solid walls with top or front actuation

## Application

For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230 mm

For wall-hung WC

For walling in and around the bearing wall – wet process

Suitable for reconstruction

## Features

- Dual flush independently adjustable with hygienic reserve
- Compatible with all ALCA flush plates except for sensor flush plates, STRIPE and NIGHT LIGHT
- The construction of the polystyrene insulation simplifies the process of walling-in, prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Material support brackets: galvanized metal
- Installation depth adjustable from 20–95 mm
- Installation height 862 mm
- Possibility of mounting in front of the wall
- Possibility of built-in remote flushing
- The cistern is made of one piece, thus ensuring 100% impermeability
- Dispenser for WC cistern tablets included
- Sliding rail holder for the waste connector can be set to eight positions between 0–93 mm
- Galvanized support structure with four hinged brackets for easy installation
- Prepared for connecting a bracket with a DG 1/2" conversion for bidet seats and sprays
- Water supply from rear / top / left / right
- Angle valve with the ability to connect to the Mepla piping system
- Maintenance work without using any tools
- Installation depth 170 mm
- This technical solution allows anchoring to an uneven surface of the back wall where a cut out was made, in the range of 50 mm
- Removable piece of polystyrene allows for easy access during installation

## Scope of supply

- Fixation material for fixing the WC pan: threaded rod M12 – 2 pcs, washers – 4 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Fixation set: screw Ø8x60 dowel – 4 pcs, dowel Ø12 – 4 pcs, combi screw M10 – 2 pcs
- Elbow waste connector HT 90/110 polyethylene, PE-HD
- The 2 piece cover of the service opening is simply adjustable
- Cistern with fill and flush valve
- Galvanized frame including supporting structure
- End-caps set for protecting the connecting holes during installation of the system
- Set for inserting toilet tablets
- Threading 1/2" for water connection with an integrated angle valve 1/2"–3/8"
- Drainage seal, PP connector, connector seal
- Inlet seal, PP outlet, wrapping seal

## Order number, Logistic information

| Code      | EAN           | Weight<br>(piece   packing   palett) | Dimensions<br>(piece   packing) | Quantity<br>(packing   palett) |
|-----------|---------------|--------------------------------------|---------------------------------|--------------------------------|
| AM119/850 | 8595580563387 | 10,56   10,56   189,0 kg             | 1040x465x180   1200x800x460 mm  | 1   16 pcs                     |

## Warranty

2/15 years \*

## Norms

EN 14124, EN 14055

## Technical specifications

- Recommended range of water pressure 0,3-0,5 MPa
- Functional range of water pressure 0,05-1,6 MPa
- Hygienic reserve 3 l
- Small flush 2,5-3,5 l
- Water volume in the cistern 9 l
- Water connection from the back or top via mounting holes G1/2 "
- Factory setting of small flush 3 l
- Factory setting of large flush 6 l
- Big flush 6-9 l
- Load test 400 kg

