

APZ115-650 Marble Low

Shower drain without edge with grid for embedding tiles

Application

For wheelchair access

For sites with limited floor height

For drainage of floor-level showers

For installation into open spaces or near the wall of the shower area

For use of various types of floor coverings

For indoor use


Features

- Elegant design thanks to the grid for embedding tiles without a stainless steel frame
- The collar and trap are protected by foil, and the channel itself by a polystyrene insert
- Trap material: polypropylene
- Shower drain material: stainless steel 2 mm, AISI 304, DIN 1.4301
- Mechanically cleanable trap up to the waste pipe
- Linear drain from stainless steel (hardened by pickling, passivation and electrochemical polishing)
- Self-adhesive tape for quality waterproofing
- Trap firmly connected to the drain 100% waterproofing
- Installation height from 70 mm
- Adjustable height
- The high flow rate is achieved due to the double compartment trap system
- 25 years guarantee

Scope of supply

- Dismantling hook
- Fixation set: screws Ø6×50 2 pcs, dowels Ø10 2 pcs
- Installation trough cover polystyrene
- Protective foil covering for the drain edges and odour trap
- Protective film for trap inlet
- $\stackrel{\cdot}{\operatorname{Grid}}$ for gluing various types of floor coverings
- Template for cutting tiles on the grid
- Self-adhesive waterproofing tape
- The shower drain is assembled with the odour trap





Order number Logistic information

Order Hamber, Eoglistic Information				
		Weight	Dimensions	Quantity
Code	EAN	(piece packing palett)	(piece packing)	(packing palett)
AP7115-650	8595580565466 650 mm	4.60 36.81 130.4 kg	720×205×160 815×370×700 mm	8 24 pcs

Warranty

2/25 years *

Technical specifications

- Total installation height 70-97 mm
- Minimum thickness of concrete 70 mm
- Resistance of odour trap against the pressure 575 Pa
- Waste pipe diameter 40 mm
- Flow rate 35 l/min
- Load class K3 300 kg
- Odour trap 28 mm

