


# **APV32BLACK**

Floor drain 105×105/50 mm straight outlet, stainless steel grid black-matt, combined odour trap SMART





#### Application

For wheelchair access

For drainage of floor level showers

For the interior, where it is not expected to regularly use the drain (laundry, boiler

rooms, cellars)

#### **Features**

- Color: black-matt
- Side connection to waste Ø50 mm
- Insulation collar for connection to waterproofing of the building
- Combined odour trap SMART
- Compatibility with floor drains parts including wet, dry and combined odour trap SMART
- Material: polypropylene resistant to mechanical, chemical and thermal damage
- Material: stainless steel AISI 304, DIN 1.4301
- Mechanically cleanable trap up to the waste pipe
- Stainless steel grid 102×102×5 mm
- Water column and mechanical flap effectively prevent the penetration of odours from the sewer
- Height adjustable throat 9–95 mm

## Scope of supply

- Design stainless steel grid
- Floor drain throat 105×105 mm
- Combined odour trap SMART
- Seal kit
- Drain body Ø50 mm, straight outlet

### Order number, Logistic information

|            |               | Weight                     | Dimensions                   | Quantity           |
|------------|---------------|----------------------------|------------------------------|--------------------|
| Code       | EAN           | (piece   packing   palett) | (piece   packing)            | (packing   palett) |
| APV32BLACK | 8595580574956 | 0.45   9.05   164.8 kg     | 160×160×138   590×430×390 mm | 20   320 pcs       |

## Warranty

/6 years \* EN 125

### **Technical specifications**

- Total installation height 138-224 mm
- Waste pipe diameter 50 mm
- Flow of the inlet grid 37 l/min
- Load class K3 300 kgOdour trap 30 mm